

Robust Exit Light with IP66 ingress protection and highest IK10 impact resistance perfect for harsh outdoor and wet applications.

Features

- IP66 weatherproof, IK10 rated
- High performance LED technology
- Advanced Lithium batteries
- Maintained / non-maintained operation
- 24m viewing
- Wall surface mounted
- Low energy consumption
- Large terminal blocks
- Designed in accordance with AS/NZS 2293



Ordering Information

Part Number	Description	Box Quantity
MRX-EXWPW	CYCLONE LED Weatherproof IP66 Wall Mount 24m Maintained Exit Light c/w Lithium Battery	1

Specifications

Input	Wiring	Lamp	Mode	Viewing	Battery	Autonomy	Mounting	IP	Compliance	Classification
230VAC 50Hz	Hardwired into terminal block	2W LED Strip 50,000 hours	Maintained, Non-Maint	24m	LiFePO4	> 120 mins	Wall, surface mount	IP66	RCM, AS/NZS 2293, AS/NZS 60598.1	C0 E2.5 C90 E1.6

Dimensions



Length	Width	Height	Weight
375mm	135mm	185mm	2.5kg

Spacing Table and Mounting Heights

NATA Classification	MOUNTING HEIGHT			
	2.1m	2.4m	2.7m	3.0m*
C0 - E2.5	5.6	5.8	5.8	6.0
C90 - E1.6	4.8	4.8	4.8	4.4

* Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1